



Model IQ283B

Basic Hotel Guest Room Telephone

Feature List

- 6 year warranty
- Data port
- Ringer light
- Line powered
- Redial key (optional)
- Ringer pitch control
- Message waiting light
- Ringer volume control
- Desk or wall mountable
- Hearing aid compatible
- Recall/Transfer key (optional)
- Soft feet and 3 metre curly cord
- · Available in black, ash-cream or red
- Customisable faceplate (example pictured below*)

*Faceplates can be customised with 4 colour printing



- guest room phone (e.g., all buttons)
 - hotline/taxi phone (e.g., some buttons)
 - yellow phone (see example)





Brief Specifications of Interquartz IQ283B

PBX Recall/Transfer Timing*

Faceplate*
Hotline operation

SKUS: IQ283BB (Black), IQ283BR (Red), IQ283BA (Ash Cream)

Brief Specifications of Interqua	rtz 1Q283B	SKUS: IQ283BB (Black), IQ283BR (Rec	3), IQ283BA (ASN 1	Cre
Line type and Dial Mode	Analogue 2-wire, Tone (DTMF)			
Data Port	2 wire analogue. Shared mode defa	ult, optional split mode		
Memory Retention	Non-volatile memory (permanent re	etention without power)		
Power Source	Line powered. Batteries NOT requi	red		
Redial Function	32 digits			
Ringer Lamp	Super bright LED and Neon tube			
Message Waiting light	Suits 80VDC signal			
Dimensions	Width: 160mm; Length: 231mm;	Height: 83.5mm		
Ringer	Electronic with Hi/Lo/Off settings; 80	dBA at 30cm		
Line Cord and Plug	3m line cord & plug (suits RJ11/12/	14/45)		
Wall Mount Kit	Wall Mount Kit No. 3 (order separately	y)	-	
Operating Temp and Humidity	Temperature: 0-40° C; Humidity:	95% RH max, No dew forming	TELEPERMIT	K
Regulatory Compliance	Complies with ACMA/Austel/NZ Tele	epermit standards	<u> </u>	\subseteq
Acoustic Shock Protection	Complies with AS/ACIF S004: 2004	 Instantaneous – 123 dB SPL, Continue 	ous – 120 dBA	
Colour and external casing material	Ash and Black ABS plastic			



Line loop. No auto-dialling.

Paper, optional 4 colour printing, covering is spray coating or plastic mylar sheet (project dependent)