

Model IQ283BR

Basic Red Telephone

Feature List

- 6 year warranty
- Message waiting light
- Data port
- Ringer light
- Line powered
- Ringer pitch control
- Ringer volume control
- Desk or wall mountable
- Hearing aid compatible
- Redial key (optional)
- Recall/Transfer key (optional)
- Soft feet and 3 metre curly cord
- Available in black (above) or ash-cream (bottom**)
- Customisable faceplate*



**Faceplates can be customised with 4 colour printing

Applications:

- ✓ guest room phone (e.g., all buttons)
- ✓ emergency phone (e.g., no buttons)
- ✓ hotline/taxi phone (e.g., some buttons)

Brief Specifications of Interquartz IQ283BR

Line type and Dial Mode	Analogue 2-wire, Tone (DTMF)
Data Port	2 wire analogue. Shared mode default, optional split mode
Pause	Manual and storable pause of 1 second
PBX Recall/Transfer	100 milliseconds Timed Break
Power Source	Line powered. Batteries NOT required
Redial Function	32 digits each
Ringer Lamp	Super bright LED and Neon tube
Message Waiting light	80VDC signal
Dimensions	Width: 160mm; Length: 231mm; Height: 83.5mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA at 30cm
Line Cord and Plug	3m line cord & modular plug (suits RJ11/12/14/45)
Wall Mount Kit	Wall Mount Kit No. 3 (order separately)
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with ACMA/Austel/NZ Telepermit standards
Acoustic Shock Protection	Complies with AS/ACIF S004:2004. Instantaneous - 123 dB SPL, Continuous - 120 dBA
Colour and external casing material	Ash and Black ABS plastic
Faceplate*	Paper, optional 4 colour printing, covering is spray coating or plastic mylar sheet (project dependent)

