

## Model IQ283P

### Premium Hotel Guest Room Telephone

#### Feature List

- 6 year warranty
- Data port
- Ringer light
- Line powered
- Ringer pitch control
- Redial key (optional)
- Message waiting light
- Ringer volume control
- Desk or wall mountable
- Hearing aid compatible
- Recall/Transfer key (optional)
- Soft feet and 3 metre curly cord
- 10 pre-programmable guest service keys
- Available in ash cream (top) or black (bottom)
- Customisable faceplate\* (example above, right)
- Permanent memory retention without external power
- Electronic speaker volume control



*\*Faceplates can be customised with 4 colour printing*

#### Applications:

- Hotel/motel guest room
- Aged care/assisted living residence
- Bushfire refuge network

#### Brief Specifications of Interquartz IQ283P

SKUS: IQ283PB (Black), IQB283PA (Ash Cream)

Line type and Dial Mode	Analogue 2-wire, Tone (DTMF)
Data Port	Shared mode standard, optional split mode
10 Memory Buttons	32 digits each
Pause	Manual and storable pause of 1 second
PBX Recall	100 milliseconds Timed Break
Memory Retention	Non-volatile memory (permanent retention without power)
Power Source	Line powered. Batteries NOT required
Redial Function	32 digits
Ringer Lamp	Super bright LED and Neon tube
Message Waiting light	80VDC signal
Dimensions	Width: 160mm; Length: 231mm; Height: 83.5mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA at 30cm
Line Cord and Plug	3m line cord & modular plug (suits RJ11/12/14/45)
Wall Mount Kit	Wall Mount Kit No. 3 (order separately)
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with ACMA/Austel/NZ Telepermit standards
Acoustic Shock Protection	Complies with AS/ACIF S004: 2004. Instantaneous – 123 dB SPL, Continuous – 120 dBA
Colour and external casing material	Ash and Black ABS plastic
Faceplate*	Paper, optional 4 colour printing, covering is spray coating or plastic mylar sheet (project dependent)

